

SRS Wiolin Hypoid-Getriebeöl 85W-140



Gear Oil for Drive Axles

February 2019

Characteristics

SRS Wiolin Hypoid-Getriebeöl 85W-140 is blended from selected base oils with carefully adapted additives. Its viscosity is chosen to ensure both no channelling at low temperatures and high lubrication safety at high temperatures.

Application

SRS Wiolin Hypoid-Getriebeöl 85W-140 is intended for very high loaded hypoid meshed axles, bevel and spur gears, steering gears and not synchronized gear boxes in vehicles and machines.

Specifications

- SAE Grade 85W-140
- API GL-5
- MIL-L-2105 C/D

Approvals

- ZF Approval Number ZF000443
ZF TE-ML 16D, 21A

Recommendations

- Volvo 97310
- DAF

SRS Wiolin Hypoid-Getriebeöl 85W-140 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Wiolin Hypoid Getriebeöl 85W-140
SAE Grade	SAE J 306	85W-140
Density at 15°C	DIN 51 757	0.906
Dyn. Viscosity at -26°C	DIN 51 398	-
Dyn. Viscosity at -12°C	DIN 51 398	89,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	337
Kin. Viscosity at 100°C	DIN EN ISO 3104	24.7
Viscosity Index (VI)	DIN ISO 2909	95
Flash Point COC °C	DIN ISO 2592	220
Pour Point	DIN ISO 3016	-21
FZG-Test A/8.3/90	DIN ISO 14635	>12

The above values may vary within the commercial limits.

Made in Germany