

SRS Violin ATF III



Automatic Transmission Oil

February 2024

Characteristics

SRS Violin ATF III is a red coloured automatic transmission fluid made from selected base oils and a high performance additive package. SRS Violin ATF III has very good wear-, corrosion- and oxidation protection and a high friction stability.

Application

SRS Violin ATF III is an automatic transmission fluid for automatic and manual transmissions, auxiliary drives, clutch-, steering- and hydraulic systems. SRS Violin ATF III can be used wherever an automatic transmission oil according to Ford MERCON and General Motors ATF Dexron III G, IIE and IID is required. According to H55.6335.XX, Voith recommends to use SRS Violin ATF III at standard change intervals of up to 60,000 km. It can also be used without any problems in automatic transmission where the MB specifications MB 236.5, 236.6 or 236.7 are required.

Specifications

- General Motors ATF Dexron III H
- Ford Mercon

Approvals

- MB-Approval 236.1
- DTFR 13C100
- DTFR 13C170 (MB 236.9)
- MAN 339 Typ Z1
- MAN 339 Typ V1
- MAN 339 Typ L1
- ZF Freigabenummer ZF000439
- ZF TE-ML 04D, 14A
- Voith H55.6335.XX

Recommendations

- Volvo 97340
- Volvo 97341
- Caterpillar TO-2
- Allison C-4
- Allison TES 389
- MAN 339 Typ L2
- MB 236.9
- ZF TE-ML 05L, 09, 21L

SRS Violin ATF III is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Violin ATF III
Colour		DIN ISO 2049	red
Density at 15°C	g/cm ³	DIN 51 757	0.860
Dyn. Viscosity at - 40°C	mPa s	DIN 51 398	18,500
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	35.7
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	7.4
Viscosity Index (VI)		DIN ISO 2909	180
Flash Point COC	°C	DIN ISO 2592	215
Pour Point	°C	DIN ISO 3016	< - 50

The above values may vary within the commercial limits.

Made in Germany